







2 years warranted, 10 years spare part keeping guarantee.

TECHNICAL SPECIFICATIONS

Engine : 18 Hp. Briggs Stratton

Twin Cylinder, 4 Stroke, Air cooled, OHV, Electric started (Marched), Charged.

Fuel Consumption : 4 - 4,5 Lt. / H.

Blower : Radial Fan.

High Pressure Pump : Gear pump 0 - 30 Bar.

Tanks : Formulation Tank : 60 Lt. Fuel Tank : 22 Lt. Flush Tank : 5 Lt.

Tank Material : Polyethylene.

Formulation Consumption : Nozzles: 0 - 20 Lt / H. (Adjustable)

Battery : 12 Volt Dc. 60 ah.

Spraying Distance : 50 m.

Dimensions : 110 cm. x 99 cm. x 160 cm. (Lx W x H) (Chassis dimensions.)

Weight : 150 Kg.

www.WhiteFog.com





Fogging head:

Fogging difficult areas where vehicles, trucks can not get in, where the road conditions are inconvenient is possible thanks to rotating head which allows 360°.



3 meter long, pesdicide and corrosion resistant system existing on the machine.



Thermal fogging:

Fogging with droplets between 10 - 30 microns. (Adjustable)

Some superior specifications compared to other thermal fogging machines;



Strong engine



- Rotating fogging head



- Anti shock



- Very strong air flow





Fogging gun



- Ergonomic Remote Control 6 m. cable



Long lasting On/Off valve system

"Wireless Remote Control", "Rear View Camera" customized specifications can be added.

Machines are 2 years warranted for possible manufacturing defects. 10 years spare part keeping guarantee.

Non stop 50 hours working capacity.

200 lt. capacity pesticide and corrosion resistant formulation tank is made from polyethylene material.

The scale system on storage is easily mountable/unmountable.

Even under maximum performance usage the sound pollution is below 80 decibel.

The machine in dimension and weight is suitable for pick-up trucks/delivery cars.



























WHITE FOG Co.

www.WhiteFog.com