

Economic Mist Blower



TECHNICAL SPECIFICATIONS

Engine	: 18 Hp. Briggs Stratton (Made in USA), Gasoline, Twin Cylinder, 4 Stroke, Air cooled, OHV, Electric started (Marched), Charged, Alternative recoil starter.
Fuel Consumption	: 4 - 4,5Lt. / H. (Changeable with engine speed)
Blower	: Radial Fan.
High Pressure Pump	: Piston pump.
Tanks	: Formulation Tank : 200 Lt. Fuel Tank : 30 Lt. Flush Tank : 30 Lt.
Tank Material	: Polyethylene.
Formulation Consumption	: ULV Nozzles : 0 - 30 Lt / H. (Adjustable) Mist Nozzles : 0 - 200 Lt / H. (Adjustable) Spraying Gun : 100 - 200 Lt. / H. (Adjustable)
Battery	: 12 Volt Dc. 60 ah.
Spraying Distance	: Nozzles : 30 m. Spraying Gun : 12 m. and 3 m. (Two function.)
Dimensions	: 110 cm. x 99 cm. x 160 cm. (L x W x H) (Chassis dimensions.)
Weight	: 240 Kg.

Spraying head :




Anti-drip spraying nozzles can be adjusted in different spraying angles and estimated. Some spraying nozzles can be deactivated upon necessity, Spraying nozzles are resistant to pesticides and corrosion. Spraying difficult areas where vehicles, trucks can not get in, where the road conditions are inconvenient is possible thanks to rotating head which allows 360°.

Spraying gun :



50 meter long, high pressure, pesticide and corrosion resistant system existing on the machine. The trigger on the spraying gun allows on/off spraying.

Micron sizes :



ULV spraying function

Long lasting spraying with droplets average 25 microns.

Mist spraying function

Long lasting spraying with droplets average 70 microns.

Spraying gun function

Long lasting spraying with droplets average 100 or 300 microns.

Some superior specifications compared to other ULV and Mist Spraying machines ;



- Strong engine



- Changeable nozzles
- Rotating spraying head



- Anti shock



- Very strong air flow



- Strong pressure pump



- Spraying gun



- Ergonomic Remote control
6 m. cable



- Long lasting On/Off valve system

"Wireless Remote Control", "Electrostatic", "Rear View Camera" customized specifications can be added.

Machines are 2 years warranted for possible manufacturing defects. 10 years spare part keeping guarantee.

Non stop 50 hours working capacity.

200 lt. capacity pesticide and corrosion resistant formulation tank is made from polyethylene material.

The scale system on storage is easily mountable/unmountable.

Even under maximum performance usage the sound pollution is below 80 desibel.

The machine in dimension and weight is suitable for pick-up trucks/delivery cars.



WHITE FOG Co.

Street: 6169 No: 18/A Karacaoglan Mah.

Bornova / İzmir - TURKEY

Tel: +90 232 472 11 83

E-mail : info@whitefog.com

www.WhiteFog.com