

**SM 900**  
Thermal Fogger



#### TECHNICAL SPECIFICATIONS

Engine	: 42.1 Kw (57.3 hp)
Burn Cell Frequency	: 36.200 Kcal / H.
Formulation Tank	: 100 Lt.
Fuel Tank	: 4.5 Lt.
Formulation Tank Pressure	: 0.4 Bar
Fuel Tank Pressure	: 0.2 Bar
Battery	: 12 Volt
Formulation Consumption	: 0 - 110 Lt / H. (Adjustable with nozzles)
Fuel Consumption	: 4.5 Lt / H.
Weight	: 80 Kg.
Dimensions	: 199 cm. x 100 cm. x 55 cm. ( L x W x H )

Vehicle Mounted White Fog thermal fogging machine "SM 900" are especially designed from best quality materials, to be mounted on vehicles and feature a remote control system for effective outdoor and indoor treatments. These units can be operated perfectly from the inside of the driver cabin. They include an 12v dc electric start system for reasonable operation of start/stop and fogging. The most effective and economical treatments of their kind (Thermal Foggers) in large areas and spaces, kill all the flying and crawling insects.

**Where to Use?**

Fogging in agricultural and rural areas (cotes, barns, poultry houses); plant protection in greenhouses and plantations, additionally functions as an anti freezer in green houses.

Stock protection in silos, store rooms (food and agricultural products, textiles and tobacco)

Public health and hygiene in the human area. Vector Control (Malaria, Dengue, Chikungunya etc). Kills all the flying and crawling insects, mosquito. Used at canalizations, hotels, amusement parks, golf courses, military sites, holiday camps and villages, green fields and forests, marshlands, factories, winter-summer houses. Used under municipalities public health and hygiene.

Odor control around marshlands, canalizations, wastewater-affluent, mass garbage areas.

**Some superior specifications compared to other "Vehicle Mounted Thermal Fogging" machines ;**



WHITE FOG Co.

Street: 6169 No: 18/A Karacaoglan Mah.

Bornova / İzmir - TURKEY

Tel: +90 232 472 11 83

E-mail : thewhitefog@gmail.com

[www.WhiteFog.com](http://www.WhiteFog.com)