



TECHNICAL SPECIFICATIONS

Drive Motor	: 7.5 kW Electric Motor	Formulation Tank	: 100 L stainless steel
Power Supply	: 3-phase 360 - 500 V AC	Fogging Distance	: Up to 125m
Power Consumption	: 12 A at 400 V	Control	: Manually or automatically Automatic use via optional accessories (timer, remote control)
Supply frequency	: 50 - 60 Hz	Frame	: Stainless steel with removable drawbar, Towing coupling for vehicles and optional trolley
Fuse Protection (delay action)	: 25 A	Wheels	: 4 soft floor castors / optionally pneumatic tires, 2 swivel castors and 2 fixed castors each
Blower	: Side channel blower with frequency converter	Weight (kg)	: 175
Working Pressure (bar)	: 0.3	Dimensions LxWxH (cm)	: 160 x 76 x 195
Output (l/h)	: Freely adjustable Ideal: 43 l/h for ULV usage Max : 73 l/h	Timer	: Optional
Droplet Size	: < 20 microns	Remote Control	: Optional
Solution System	: Hose pump with suction hose Suction filter		
Solution Line	: Viton, stainless steel, PVC		
Number Of Spray Nozzles	: 4 spray nozzles 360° adjustable		
Telescopic mast	: Freely adjustable Minimum 1.95m above ground Maximum 4.3m above ground		

WHITE FOG

Street: 6169 No: 18/A Karacaoglan Mah.
Bornova / Izmir - TURKEY
Tel: +90 232 472 11 83
E-mail : info@whitefog.com

www.WhiteFog.com