



TECHNICAL SPECIFICATIONS

Engine : 18 Hp. Briggs Stratton (Made in USA), Gasoline, Twin Cylinder, 4 Stroke, Air cooled,

OHV, Electric started (Marched), Charged, Alternative recoil (Cord) starter.

Blower (Air Pump) : Roots Blower X1 - 10.6 m³ / Min., 3600 rpm.

Blower Connection : Direct connection.

Pressure (Bar) : 0.4 Bar.

Tanks : Cold Fogging Tank : 50 Lt. Thermal Fogging Tank : 50 Lt. Fuel Tank : 22 Lt. Flush Tank : 5 Lt.

Tanks Material : Stainless steel.

Formulation Consumption : 0 - 530 ML. / Min. (Adjustable with flow rate controller)

Fuel Consumption : 1-1,5 Lt. / H. (Changeable with engine speed)

Remote Control : Remote control on/off, Engine start/stop, ULV Spraying on/off, Thermal Fogging on/off,

Flush on/off, Automatic nozzles up-down and right-left switches.

Battery : 12 Volt Dc. 60 Ah.

Nozzles : Automatic 4 Cold fogging nozzles, 1 Thermal nozzle, 1 ULV spraying and 1 Thermal gun.

Dimensions : 120cm. x 99cm. x 85cm. (L x W x H)

Weight : 240 Kg.

Shipping Dimensions : 138cm. x 108cm. x 90cm.

Shipping Weight : 340 Kg.

www.WhiteFog.com





18 Hp. Briggs Stratton (Made in USA), Gasoline, Twin Cylinder, 4 Stroke, Air cooled, OHV, Electric started (Marched), Charged, Alternative recoil (cord) starter.



ULV 1200 Professional Automatic Nozzle has patented 4 nozzles system.

%20 insecticide saving, 4 units 360° rotating point, 45° up-down, 180° left-right rotating spraying head.

Each nozzle has micron size controller, It can fogging 10µm and 30µm for mosquitoes and black flies at the same time.





Cold Fogging Function

10 - 20 μm size for mosquitoes. (The optimum droplet size for space spraying against mosquitoes is 10–20 μm.)

ULV Spraying Function

20 - 30 μm size for larger flies than mosquitoes. (Tsetse flies, black flies.)

Thermal fogging function

Oil-Based 0 - 30 µm size for mosquitoes.



ULV 1200 Professional Automatic Nozzle has "T" design remote control and 6 meters long cable with quick connector. Remote control on / off, Engine start / stop, ULV spraying on / off, Flush on / off, Thermal on/off.





ULV 1200 Professional with 50 lt. tank capacity can be used either as 50 lt. ULV spraying tank and 50 lt. Thermal fogging tank. ULV 1200 Professional with 100 lt. tank capacity can be used either as 100 lt. ULV spraying tank or 100 lt. Thermal fogging tank. 5 lt. Flush tank made of stainless steel.

22 lt. Fuel tank made of polyethylene.



3 meters long flexible stainless steel "Thermal Fogging" gun with connector.

Thermal Gun Function:

0 - 100 μm sizes. (Adjustable with flow rate for residual treatment or canalization treatment)

5 meters long high pressure, pesticide and corrosion resistant ULV spraying gun with connector. Valve on spraying gun allowing on/off spraying.

ULV Gun Function:

0 - 100 μm sizes. (Adjustable with flow rate for residual treatment or canalization treatment)



















www.WhiteFog.com