



10 μm - 20 μm - 50 μm







TECHNICAL SPECIFICATIONS

Engine : 18 Hp. Briggs Stratton (Made in USA), Gasoline, Twin Cylinder, 4 Stroke, Air cooled,

OHV, Electric started (Marched), Charged, Alternative recoil starter.

Blower (Air Pump) : Roots Blower, 10.6 m³ / Min., 3600 rpm.

Blower Connection : Direct connection

Pressure (Bar) : 0.4 Bar.

Tanks : Formulation Tank : 60 Lt. Fuel Tank : 22 Lt. Flush Tank : 5 Lt.

Tanks Material : Stainless steel.

Formulation Consumption: 0 - 530 ML. / Min. (Adjustable with flow rate controller)

Fuel Consumption : 1 - 1,5 Lt. / H. (Changeable with engine speed)

Remote Control : Remote control on / off, Engine start / stop, ULV spraying on / off, Flush on / off.

Battery : 12 Volt Dc. 60 Ah.

Nozzles : 4 nozzles. (7 units 360° rotating point)
Dimensions : 148 cm. x 75 cm. x 85 cm. (L x W x H)

Weight : 200 Kg.

Shipping Dimensions : 157 cm. x 90 cm. x 95 cm.

Shipping Weight : 286 Kg.

www.WhiteFog.com





18 Hp. Briggs Stratton (Made in USA), Gasoline, Twin Cylinder, 4 Stroke, Air cooled, OHV, Electric started (Marched), Charged, Alternative recoil starter.



ULV 1200 G1 has patented 4 nozzles system.

%20 insecticide saving, 7 units 360° rotating point, 360° up-down, 360° left-right rotating spraying head.

Each nozzle has micron size controller, It can fogging 10µm and 50µm at the same time.



Cold Fogging Function

10 - $20\,\mu m$ size for small insects.

ULV Spraying Function

 $20 - 50 \ \mu m$ size for big insects or for fungicides cover.



ULV 1200 G1 has "T" design remote control and 6 meters long cable with quick connector. Remote control on / off, Engine start / stop, ULV spraying on / off, Flush on / off.



60 Lt. ULV formulation tank made of stainless steel.

5 Lt. Flush tank made of stainless steel.

22 Lt. Fuel tank made of polyethylene.









ULV Back Up system; during pesticiding even if you face with a technical problem (ie: when remote control does not function) WhiteFog designed a back up plan for you. The second MANUEL starting system of ULVs let user to keep the work even under technical starting problem. WhiteFog's all time priority is the happiness and satisfaction of the customer which is our difference!

Machines are 1 years warranted for possible manufacturing defects. 10 years spare part keeping guarantee.

Non stop 50 hours working capacity.

Even under maximum performance usage the sound pollution is below 80 desibel.

Shock-absorbing vibration pads that cut vibration to a minimum.

The machine in dimension and weight is suitable for pick-up trucks/delivery cars.

No pre-technical knowledge needed for usage! Specially designed for easy use!

All the electronic parts of the machine, connections are simplified.

No complicated details as many of our rivals do as a policy.

WhiteFog made it simple for you; to keep the maintenance easy for allowing easy reparation all around the world.

Briefly, WhiteFog means no maintenance problem.











WHITE FOG

www.WhiteFog.com